



Everything for Inflatables

## **PVC TOLUENE FREE SINGLE PART ADHESIVE INSTRUCTIONS**

### **Product Description**

PVC Toluene Free single part Adhesive gives strong adhesion to most forms of PVC. The adhesive system is also very useful for many industrial and home applications and will bond a wide variety of surfaces including wood, canvas, leather and PVC. Always do a small test before full application.

### **Application**

1. Thoroughly clean and dry both surfaces. -PVC materials give best results if solvent wiped immediately prior to use with MEK or similar.
2. Apply a thin coat of adhesive to each surface and allow to dry for 20 minutes or until touch dry. Applying a further coat will give better results.
3. Bring the two coated surfaces together using sufficient pressure to ensure intimate contact, taking care not to trap any air pockets.

### **IMPORTANT NOTE:**

*All the information in the Data Sheet is based on practical experience and is published in good faith. However, because we have no control over the manner or conditions in which our products are used, or over work undertaken or end product manufactured by the purchaser, we cannot accept liability for results. Responsibility for ascertaining the suitability of products for his purposes rests with the purchaser. All conditions, representations, statements, warranties or guarantees whatsoever, whether express, implied or statutory, in respect of any goods manufactured, sold or supplied by us are hereby expressly excluded and we accept no liability in respect of any claim for damage or consequential loss caused to any property arising directly or indirectly out of the use of our products or goods.*