



# ANTIVEGETATIVA PER ELICHE

## STERN DRIVES AND PROPELLERS ANTIFOULING

Special antifouling for best protection of stern drives and propellers. The exceptional adhesive property and great hardness of ANTIVEGETATIVA PER ELICHE make it resistant to the great strains placed on these parts of the boat.

It should be applied as soon as the boat is hauled to allow the product to dry completely and to reach maximum hardness before being re-launched.

It requires extensive cleaning and preparation: de-grease with detergents, sand finely down to bright metal, rinse with fresh water.

Apply directly on the stern drives and the propeller in case of "TRASPARENTE"

Apply after one coat of PRIMER ELICHE in case of coloured version. Apply two coats of ANTIVEGETATIVA PER ELICHE waiting at least 24 hours between each coat. Launch after a minimum of 24 hours.



|                     |  |
|---------------------|--|
| thinner:            | <b>Diluyente per antivegetative</b>        |
| coverage:           | <b>8 MQ/LT</b>                             |
| overcoating:        | <b>12 h.</b>                               |
| complete drying     | <b>24 h</b>                                |
| launching:          | <b>min. 24h</b>                            |
| suggested n° coats: | <b>2</b>                                   |
| dry film thickness: | <b>80 microns</b>                          |
| solids content:     | <b>47%</b>                                 |
| flash point:        | <b>37° C.</b>                              |
| specific weight:    | <b>1,35</b>                                |
| airless:            | <b>30/1 - 0.013 - 0.017</b>                |
| spry:               | <b>2 - 3 Kg/cm<sup>2</sup> - 1.2 - 1.4</b> |

### AVAILABLE:

transparent 250 ml tin  
white 250 ml tin  
black 250 ml tin  
grey\* 250 ml tin  
dark gray\*\* 250 ml tin

\* old volvo penta \*\* new volvo penta

